



## W7-X Highlights OP2.2 / OP2.3 – SOL/Divertor



EUROfusion


D. Gradic for the W7-X Team




This work has been carried out within the framework of the EUROfusion Consortium, funded by the European Union via the Euratom Research and Training Programme (Grant Agreement No 101052200 — EUROfusion). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.

# Addressing divertor overloads


- **Higher heating powers ( $\geq 6$  MW) caused divertor overloads limiting operation in several configs, most critical in FTM**
  - Overloads were often in shadowed regions where deposition was not anticipated by early modeling
- **Mitigation strategies developed and tested**
  - Modify edge topology with control coils/planar coils
  - Sweep strike lines with AC current in control coils
  - ECCD to control strike line location
  - **Impurity seeding: most reliable and universally applicable approach**



# Seeding in combination with High power/high performance programs → safe divertor



High power (12 MW), **feedforward** Neon seeding with safe divertor in FTM




High performance with **feedback** Neon seeding with safe divertor in FTM

# Direct control of radiated power $P_{rad}$ through feedback-controlled impurity seeding




- $P_{rad}$  determined in real time from bolometer signal
- Seeding valve voltage adjusted with PID controller to admit impurity gas (neon or nitrogen) to achieve desired  $P_{rad}$
- $P_{rad}$  values up to 6 MW have been achieved and steadily maintained, sustaining fully-detached plasmas



generated Fri Apr 4 18:35:08 2025 - version 3.0 - contact: astechow@ipp.mpa.de - data missing: ['CXRS ne', 'assetpoint', 'CXRS core', 'ICRH']

# 1.8 GJ injected energy record with “detached scenario”




6 min plasma (363s) with  $P=4.9$  MW → **new injected energy record of 1.785 GJ**

**Use of Feedback-regulated Neon seeding ( $P_{rad}$ -target = 4.3 MW) to keep divertor safe → radiative detachment**

Use of all 11 gyrotrons in „power stabilisation mode“

Program stopped by ECB cooling water rise from 18°C up to 29°C within 360s




**Good machine condition:** Neon-seeding & H-fueling, impurity radiation fronts and intensities stable within SOL



# First Look into a non-resonant divertor configuration at W7-X

NRD studies in CYM000+1810, all discharges succeeded at the first attempt!

- 20250520.29: NBI S4 1.8 MW + S8 1.8 MW
- 20250520.30/ 20250520.32: NBI S4 1.8 MW/ NBI S8 1.8 MW
- 20250520.31: NBI S4 1.8 MW + S8 1.8 MW modulated
- 20250520.33: NBI S4 1.8 MW modulated + S8 1.8 MW modulated



courtesy of Amit Kharwandikar

Only attempted in low-field (1.8 T), SOL radiation and divertor loads seemingly not affected by  $I_{tor}$  but observation hampered