



## Divertor concept development for the W7-X stellarator experiment




Indigo: <https://event.ipp-hgw.mpg.de/category/63/>

<https://datashare.mpcdf.mpg.de/s/EPkFnQ5TXRYoNV8>



This work has been carried out within the framework of the EUROfusion Consortium, funded by the European Union via the Euratom Research and Training Programme (Grant Agreement No 101052200 — EUROfusion). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.

# W7-X divertor setup OP3



# W7-X divertor setup OP3 – physical optimization objectives



**power  
exhaust**



1. **heat loads on PFCs should not exceed their specific, defined limits**
  - acceptable peak loads,
  - tolerable input energies to individual components, by broadening of heat load distribution (larger wetted areas),
2. **avoid localized excess heat loads** (leading edges, fast particles).

**particle  
removal**



to pump helium, the fuel gases are pumped at almost the same rate!

3. **high particle exhaust rate  $\Gamma_{\text{exhaust}}$  [a/s]** (TMPs, cryopumps)

reactor:

- $\Gamma_{\text{exhaust-He}} = \Gamma_{\text{Fusion-He}}$     **What is  $\Gamma_{\text{Fusion-He}}$  mimic in W7-X? -> NBI-He, He conc. several % <5%**

operational:

- $\Gamma_{\text{exhaust}} = \Gamma_{\text{source,wall}} + \Gamma_{\text{source,NBI}} + \Gamma_{\text{source,Pellet}} + \Gamma_{\text{source,gasinlet}}$

**impurity  
control**



4. **acceptable net erosion**
5. **screening/retention of impurities** in divertor plasma
  - increase power dissipation in the divertor plasma/SOL (by seeding),
  - prevent core radiation losses -> exhaust of impurities by friction, electric  $\leftrightarrow$  thermal forces, drift effects; reduce sputtering
  - minimize  $R_{\text{eff}}$  for impurities

# W7-X divertor setup OP3 – technical optimization objectives



**power  
exhaust**



**1. heat loads on PFCs should not exceed their specific, defined limits**

**2. avoid localized excess heat loads** (leading edges, fast particles)

- cost reduction and limitation of production time
- reduced number of target elements/cooling circuits, i.e. aggregation of target elements into few modules
- volume production of common and flat tungsten mosaic tiles with optimized number and dimensions avoiding leading edges
- reduced material removal & W coating of flat tiles to comply with 3D surface
- optimization of bonding technology between W, Cu-OFE, CuCrZr and SS
- development of He-leak-tight heat sinks by 3D AM

**particle  
removal**



**3. high particle exhaust rate  $\Gamma_{\text{exhaust}}$  [a/s]** (TMPs, cryopumps)

- optimization of target geometry to collect particles in molecular, transitional, and continuous flow regimes
- reduction of pump gap losses in molecular and transitional flow
- maintain good toroidal and poloidal plugging by the divertor plasma
- maintain small gaps in sub-divertor to minimize losses to main chamber

**impurity  
control**



**4. acceptable net erosion**

- selection of materials with low sputtering yields, low hydrogen retention

**5. screening/retention of impurities in the divertor plasma**

# W7-X divertor setup OP3 – technical constraints: TE



## geometry



1. nearly flat heat sinks with mosaic of flat W95NiFe tiles of max.  $\sim 40 \times 40$  mm
2. radially curved edge tile with constant radius  $\geq 15$  mm
  - preferred thickness before final machining  $\leq 2$  mm to enable bent edge tile
3. final machining of W based tiles is assumed to be done by wire erosion
  - poloidal direction to be straight or convex to allow use of a straight erosion wire
  - toroidal direction can be convex or concave
  - curvature limitation of TM1h, TM9h, TM1v
4. gaps between tiles inside target module  $> 0.5$  mm, preferably  $\sim 1.4$  mm
  - 1.4 mm gap  $\rightarrow$  leading edge 0.13 mm (@  $5^\circ$  incidence angle)  $\rightarrow$  heat flux limit ?
5. gaps between target modules  $> 5$  mm (thermal expansion and assembly inaccuracies)
  - $0.43 + \sim 0.4$  (installation) = 0.8 mm leading edge  $\rightarrow$  where allowed ?
  - longer slits in toroidal direction  $\rightarrow$  erosion in gaps due to gyro effects
6. final tile thickness:  $> 0.5$  mm (erosion),  $> 3$  mm (Cu sputtering)

## cooling water supply



1. 12x supply line  $\varnothing 32$  mm with 5 l/s, static pressure 10 bar
  - limits:  $\Delta T = \sim 60$  K,  $\Delta p = 15$  bar
2. optimize cooling channel geometry
3. corrosion of tungsten alloys, Ni coating?

## handling / installation



1. mass per target module  $< \sim 60$  kg
2. size similar to OP2 divertor  $\sim 0.25$  m<sup>2</sup> ( $400 \times 600$  mm<sup>2</sup> up to  $300 \times 800$  mm<sup>2</sup>)
3. installation tolerance: relative between modules  $\sim 0.4$  mm, absolute **?? mm** -> **experiments/modeling/asymmetries (top-down, drifts)?**
4. fix points are  $\varnothing 32$  mm inlet /outlet which should be near to each other
5. additional flexible pin support to make module statically determined

# W7-X divertor setup OP3 – technical constraints: baffle



## geometry



1. 250 kW/m<sup>2</sup> radiation load (limited by cooling water supply assuming 0.4 m<sup>2</sup> module size)
2. **1 MW/m<sup>2</sup> local convective load on 1 W based tile (~0.1x0.1 m<sup>2</sup> → 10 kW)**
3. no intersection of plasma exposed surface with outermost surface of magnetic island
4. chamfered W based tiles to allow for default 1.5 mm tolerance
5. spring loaded contact between tiles – sigraflex – heat sink to moderate thermal stress

## cooling water supply




1. use of existing OP2 water infrastructure
2. 12x 0.5 l/s = 6 l/s water available per divertor unit for the baffles,  $\Delta T \leq 50K \rightarrow 12 \times 100 \text{ kW}$
3. exposed baffle area 3.86 m<sup>2</sup> /divertor unit  
→ average heat load  $12 \times 100 / 3.86 = 310 \text{ kW/m}^2$
4. inlet & outlet  $\varnothing 12 \times 1 \text{ mm}$  flexible pipe

## handling / installation



1. separate heat sink plate and support structure. heat sink fixations accessible from plasma side
2. mass per heat sink preferably  $< \sim 40 \text{ kg}$ , size similar to OP2 baffles  $\sim 0.40 \text{ m}^2$  (11 mm Cu = 100 kg/m<sup>2</sup>)
3. statically determined support
4. simple installation consoles to release mass before fixation
5. 4 mm W based tiles of  $\sim 0.1 \times 0.1 \text{ m}^2$  with fixation accessible from plasma side ( $< 1 \text{ kg /tile}$ )
6. water connection accessible

# W7-X – technical constraints: NBI beam dump



- loads depend on plasma absorption up to  $40 \text{ MW/m}^2$  at zero absorption
- pulse duration limited by heat load capacity of heat sinks / tiles / bolts
  - ➔ up to one second for a single source

temperature limits:

CuCrZr <  $500 \text{ }^\circ\text{C}$ , CFC <  $1200 \text{ }^\circ\text{C}$ , Graphite <  $1800 \text{ }^\circ\text{C}$ , W <  $1300 \text{ }^\circ\text{C}$



cyclic strain limit: stainless steel pipe <  $0.2 \%$

flexural stress limit: graphite <  $30 \text{ N/mm}^2$ , W <  $700 \text{ N/mm}^2$

bolt stress TZM: <  $700 \text{ N/mm}^2$

elastic play in bolt springs:  $1 \text{ mm}$

thermo-mechanical assessment by E5-E is pending -> design improvements?



# W7-X divertor setup OP3 – optimization criteria

**power  
exhaust**



1. **heat loads on PFCs should not exceed their specific, defined limits**
2. **avoid localized excess heat loads** (leading edges, fast particles).
  - $p < 10 \text{ MW/m}^2$  steady state -> GLADIS tests with  $15 \text{ MW/m}^2$
  - $p_{\text{max}} = 10 \text{ MW/m}^2$  steady state,
  - $T_{\text{max}}$  (WNiFe)  $< 1300 \text{ }^\circ\text{C}$ , (OFE-Cu)  $< 600^\circ\text{C}$ , CuCrZr  $< 475^\circ\text{C}$ , channel  $< 200^\circ\text{C}$
  - wetted areas  $> 1 \text{ m}^2$ , incidence angles  $< 5^\circ$

**particle  
removal**



3. **high particle exhaust rate  $\Gamma_{\text{exhaust}}$  [a/s]** (TMPs, cryopumps)  
by ensuring a high exhaust efficiency, combined with throttle

$$\eta_{\text{exhaust}} = \Gamma_{\text{Exhaust}} / \Gamma_{\text{Neutral}} = \eta_{\text{collection}} * \eta_{\text{removal}}$$

- neutralize high ion influx in divertor
- high collection efficiency
- high removal efficiency
- high plugging efficiency

$$\Gamma_{\text{ion divertor}} \rightarrow \Gamma_{\text{neutra}} \quad \text{He enrichment? Reactor scaling?}$$

$$\eta_{\text{collection}} = \Gamma_{\text{Pumpgap}} / \Gamma_{\text{Neutral}}$$

$$\eta_{\text{removal}} = \Gamma_{\text{Exhaust}} / \Gamma_{\text{pumpgap}}$$

$$\eta_{\text{plugging}} = \Gamma_{\text{Divertor Recycling}} / \Gamma_{\text{Recycling}}$$

**impurity  
control**



4. **acceptable net erosion**
  - net erosion rate  $< 0.2 \text{ nm/s}$   $\rightarrow @15 \text{ y} * 40 \text{ days/y} * 1800 \text{ s/day} \rightarrow 0.22 \text{ mm}$
5. **screening/retention of impurities** in divertor plasma
  - W core concentration  $< 2e-05$

# W7-X divertor setup OP3 – optimization tools

**power  
exhaust**



**particle  
removal**

**impurity  
control**

- 1. heat loads on PFCs should not exceed their specific, defined limits (heat loads should be concentrated on the target surfaces (>95%), <5% on other components such as baffles, heat shield, panels)**
  - fast tools: EMC3-Lite, SHFP model (→ A. Kharwandikar / T. Kremeyer)
  - fast tools: EMC3-Lite for divertor plate optimization with second stage of magnetic field optimization via coil geometry/currents adjustments, application to HSX (→ B. Davies)
  - state-of-the-art: EMC3/Eirene (connecting LCFS-SOL-divertor) (→ Y. Feng, D. Boeyaert, A. Kharwandikar)
- 2. avoid localized excess heat loads (leading edges, fast particles)**
  - fast tools: EMC3-Lite, ANSYS, SHFP -> LEADERS (python code) (→ A. Menzel-Barbara) for all materials (heat sink + armor)

# W7-X divertor setup OP3 – optimization tools

$$n_{0,t} \propto \Delta x \cdot \frac{n_d}{T_{id}} \cdot \frac{(1 - f_{rad})}{A_w} \cdot P_{SOL} \quad [Y. Feng, 6. 6. 2023]$$

power  
exhaust


particle  
removal

impurity  
control



### 3. high particle exhaust rate (TMPs, cryopumps)

- fast tools: multi-chamber models, ANSYS (→ V. Haak)
- fast tools: 2D-analytical model, viewing factors (→ T. Kremeyer, S. Dräger)
- fast tools: COMSOL (→ T. Kremeyer)  
(molecular flow module,  $0.1 < Kn < 10$  (Boltzmann equ.),  $0.01 < Kn < 0.1$  (Navies-Stokes))
- fast tools: 3D-Direct Simulation Monte Carlo (DSMC) (→ A. Kharwandikar?)  
EMC3-Lite as source for the neutrals, plasma domain as sink,  
EMC3/Eirene (no collisions in volume).
- state-of-the-art: EMC3/Eirene: **evaluation**  $p_{div, neutrals} = f(n_{e,sep}, n_{e,div}, P_{input} > 10 \text{ MW}, P_{rad})$   
(→ Y. Feng, D. Boeyaert)
- state-of-the-art: DIVGAS (only sub-div region) (→ S. Varoutis, Ch. Tantos (KIT))
- neutral gas modeling [cooperation (?) with KU Leuven T. Baelmans:  
advanced fluid neutral (AFN) and hybrid fluid-kinetic approaches for the neutral particles



[T. Kremeyer, 20. 6. 2023]

# W7-X divertor setup OP3 – optimization tools

**power  
exhaust**

**particle  
removal**

**impurity  
control**




## 4. acceptable net erosion

- state-of-the-art: ERO2.0 (→ FZ Jülich (A. Kirschner, J. Romazanov))
- erosion in gaps (experiments AUG K. Krieger, ITER design) (→ A. Menzel-Barbara)


## 5. screening/retention of impurities in divertor plasma

- state-of-the-art: EMC3/Eirene, ERO2.0 (→ V. Winters, F. Reimold)

## W7-X design tools with CATIA – for modified geometries



detailed CAD geometry of  
one divertor unit



reduced grid-based stream-line model  
with limited number of grid points –  
recently developed by DE IPP Greifswald

**the modeling activities are supported by the development of efficient engineering tools in a CATIA environment that process the complex 3D W7-X design data at different levels of sophistication to promote an efficient interchange with the physics-based codes**

Training by T. Sieber to use the grid-based model within CATIA to generate data in Kisslinger format for the EMC3 modeling.

# W7-X design tools – for modified geometries



construction of 3D target surfaces based on a 2D contour in one selected phi cross section, following o-lines toroidally [A. Kharwandikar]

development of python routines for the handling of single/separate modules allowing various transformations in size, shape, position, angle [A. Menzel-Barbara]

construction of 3D target surfaces based closed flux surfaces [B. Davies]

# Priorities for the divertor development

**power  
exhaust**

**particle  
removal**

**impurity  
control**

- start with power exhaust analysis for attached conditions: definition of modified geometries meeting two criteria:
  1. keep maximum heat load below  $10 \text{ MW/m}^2$  with a heating power of at least 10 MW,
  2. keep the heat load only on the divertor targets ( $> 95\%$ ).
- evaluate modified geometries against particle removal requirements
- identify potential impurity retention drawbacks

